



# TruStop

## Crack Injection Kits™



### TruStop™ Features:

- Grout Elongation: 44%
- USDA Approved
- Environmentally Friendly
- Easy to Use
- Worker Friendly
- Can be used on virtually any surface
- Use on Cracks, Manholes, Vaults, even Dams

### Product Description:

TruStop™ Crack Injection Kits contain all you need for any crack repair, the materials are easy to use and worker and environmentally friendly. Our three part system contains, Grout, Catalyst and Injection Ports. TruStop™ Grout and Catalyst are used with HouseGuard™ Disposable Injection Guns (sold separately). TruStop™ Grout is a multi-purpose injection resin designed to seal leaking cracks, voids or fractures in concrete surfaces. TruStop™ Catalyst activates the Grout to react with moisture in the concrete surface, expanding and crosslinking to form a watertight seal. When using TruStop Grout a 15-second reaction time may be achieved by mixing 1 part of TruStop Catalyst to 8 parts Grout. Faster reaction times may be achieved by use of additional Catalyst. TruStop™ Injection Ports are 5/8" mechanical ports constructed of a brass stem, extruded rubber bladder and 1/4" X 28 grease injection type fitting. TruStop™ Crack Injection Kits come in three sizes: the TruStop™ Sample Kit, equipped with enough product to repair up to 2 cracks ; the Starter Kit, will supply you with the right amount of product to complete up to 14 cracks, and the Bulk Kit, a larger quantity of product for up to as many as 60 cracks.

#### Grout

##### TEST TYPE

Density  
 Water Absorption (Volume Confined)  
 Shear Strength  
 Tensile Strength  
 Elongation  
 Viscosity  
 Color  
 UL Listed  
 USDA Approved  
 USDOT Shipping Data

##### RESULTS

2 lbs.  
 <1%  
 17.10 PSI  
 29.30 PSI  
 44%  
 @500CPS  
 Amber  
 (NSF-61-1989)  
 YES  
 UNREGULATED, CLASS 55

##### TEST METHOD

ASTM D-1622  
 ASTM D-2127  
 ASTM C-273  
 ASTM D-1623  
 ASTM D-1623



Injection Port



8600 Berk Blvd. Hamilton, Oh 45015 ••• 800.560.5701

